



ASH AIR

This single-strip ash floor from the Lux Collection delivers a refined expression with a clean, even grade and a weightless white stain. Four-sided micro-bevelling at the edging ensures a classic, fullplank look and feel. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

| PRODUCT DESCRIPTION | | FACTS | | TECHNICAL PROPERTIES | | |
|--|-----------------------|----------------------|---------------------|--|-------------|------------------------|
| Article Number | 151N8MAKA4KW240 | Wood Species | Ash | Moisture content | EN13183 | 7%±2% |
| Surface treatment | Ultra matt lacquer | Board | 1-strip | Minimum Mean Density kg/m ³ | | >500 kg/m ³ |
| Design features | Microbevelled 4-sided | Grading | Calm (City) | Reaction To Fire | EN13501-1 | Dfl-s1 |
| Dimensions | 2420 x 187 x 15 mm | Range | Kährs Original | Formaldehyde Emission | EN717-1 | E1 |
| Weight per Package | 22 kg | Collection | Lux Collection | Content PCP | CEN/TR14823 | ≤ 5 x 10-6n |
| Area per Package | 2.72 m ² | Resandable | 2-3 times | Breaking Strength N/mm ² | EN1533 | NPD |
| Area Per Board | 0.453 m ² | Natural/Stained | Stained | Thermal Conductivity | EN12664 | 0,14 W/mK |
| DETAIL DESCRIPTION | | Brinell Value | 4, 0 | Thermal Resistance R-Value | | .11 (m2K/W) |
| | | Joint | Woodloc® 5S | Biological Durability | EN350-2 | Class 1 |
| COLOUR CHANGE | | Floor heating | Yes | CARB2 | | Compliant |
| | | Warranty | 30 years | | | |
| Stained product - noticable color change over time | | Wear-layer material | Hardwood | | | |
| | | Wear-layer thickness | 3, 5 mm | | | |
| | | Core material | Pine/Spruce/Alder | | | |
| | | Backside material | Spruce | | | |
| | | Thickness | 15 mm | | | |
| | | Installation method | Floating, glue-down | | | |
| | | EAN Code | 7393969044233 | | | |
| | | Surface Colour | White | | | |

CERTIFICATES

