



OAK BRIGHTON

This single-strip oak floor from the Sand Collection features warm butterscotch undertones, punctuated with naturally occurring knots for a lively expression. The wearing side of each board is taken exclusively from a single piece of wood, capturing the true form of the timber. The matt lacquer finish eliminates glare while protecting the wood from daily wear.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	151L87EK0VKV220	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Matt lacquer	Board	1-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Dimensions	2266 x 187 x 15 mm	Grading	Lively (Country)	Reaction To Fire	EN13501-1	Dfl-s1
Weight per Package	21 kg	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1
Area per Package	2.54 m ²	Collection	Sand Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area Per Board	0.423 m ²	Resandable	2-3 times	Breaking Strength N/mm ²	EN1533	NPD
DETAIL DESCRIPTION		Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK
Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers.		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m ² K/W)
COLOUR CHANGE		Joint	Woodloc® 5S	Biological Durability	EN350-2	Class 1
Stained product - noticeable color change over time.		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
		Thickness	15 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969041164			
		Surface Colour	White E0V			

CERTIFICATES

