



## OAK CONCRETE

The natural oil finish and sleek grey stain found on this single-strip maple floor from the Artisan Collection create a refined yet rustic expression. Knots and cracks pepper the boards, adding depth and balancing the bleached wheat highlights. Every board is carefully brushed to bring out the character of the grain and emphasise the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

| PRODUCT DESCRIPTION  |  | FACTS                       |                     | TECHNICAL PROPERTIES              |             |             |
|--|--|-----------------------------|---------------------|-----------------------------------|-------------|-------------|
| <b>Article Number</b>  | 151XCDEKFMKW190                        | <b>Wood Species</b>         | Oak                 | <b>Moisture content</b>           | EN13183     | 7%±2%       |
| <b>Surface treatment</b>   | Oil                                    | <b>Board</b>                | 1-strip             | <b>Minimum Mean Density kg/m³</b> |             | >500 kg/m³  |
| <b>Design features</b>   | Handscraped, brushed, bevelled 4-sided | <b>Grading</b>              | Dynamic             | <b>Reaction To Fire</b>           | EN13501-1   | Dfl-s1      |
| <b>Dimensions</b>  | 1900 x 190 x 15 mm                     | <b>Range</b>                | Kährs Original      | <b>Formaldehyde Emission</b>      | EN717-1     | E1          |
| <b>Weight per Package</b>  | 17 kg                                  | <b>Collection</b>           | Artisan Collection  | <b>Content PCP</b>                | CEN/TR14823 | ≤ 5 x 10-6n |
| <b>Area per Package</b>  | 2.17 m²                                | <b>Resandable</b>           | 2-3 times           | <b>Breaking Strength N/mm²</b>    | EN1533      | NPD         |
| <b>Area Per Board</b>  | 0.361 m²                               | <b>Natural/Stained</b>      | Stained             | <b>Thermal Conductivity</b>       | EN12664     | 0,14 W/mK   |
|  |  | <b>Brinell Value</b>        | 3, 7                | <b>Thermal Resistance R-Value</b> |             | .11 (m2K/W) |
|  |  | <b>Joint</b>                | Woodloc®            | <b>Biological Durability</b>      | EN350-2     | Class 1     |
|  |  | <b>Floor heating</b>        | Yes                 | <b>CARB2</b>                      |             | Compliant   |
|  |  | <b>Warranty</b>             | 30 years            |                                   |             |             |
|  |  | <b>Wear-layer material</b>  | Hardwood            |                                   |             |             |
|  |  | <b>Wear-layer thickness</b> | 3, 5 mm             |                                   |             |             |
|  |  | <b>Core material</b>        | Pine/Spruce lamella |                                   |             |             |
|  |  | <b>Thickness</b>            | 15 mm               |                                   |             |             |
|  |  | <b>Installation method</b>  | Floating, glue-down |                                   |             |             |
|  |  | <b>EAN Code</b>             | 7393969033527       |                                   |             |             |
|  |  | <b>Surface Colour</b>       | Grey FM             |                                   |             |             |
| <b>DETAIL DESCRIPTION</b>  |  |                             |                     |                                   |             |             |
| All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers. |  |                             |                     |                                   |             |             |
| <b>COLOUR CHANGE</b>   |  |                             |                     |                                   |             |             |
| Stained product - noticable color change over time.  |  |                             |                     |                                   |             |             |
| <b>CERTIFICATES</b>  |  |                             |                     |                                   |             |             |

