



**Kährs**  
QUALITY IN WOOD SINCE 1857

## OAK DAWN

This 3-strip oak floor from the Lumen Collection features warm, washed undertones, with a lighter and calmer expression than most conventional natural oak floors. Each board is carefully brushed to perfection, bringing out the faintly burnished nuances in the grain. The ultra-matt lacquer finish enhances the natural variations in the wood, creating the impression of newly sawn timber. This effectively eliminates glare while protecting the floor from daily wear.

### PRODUCT DESCRIPTION

Article Number	153N3BEK04KW240
Surface treatment	Ultra matt lacquer
Design features	Brushed
Dimensions	2423 x 200 x 15 mm
Weight per Package	23 kg
Area per Package	2.91 m <sup>2</sup>
Area Per Board	0.485 m <sup>2</sup>

### DETAIL DESCRIPTION

Even colour with minor variations. Small sized knots in limited numbers allowed.

### COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

### FACTS

Wood Species	Oak
Board	3-strip
Grading	Variation (Town)
Range	Kährs Original
Collection	Lumen Collection
Resandable	2-3 times
Natural/Stained	Natural
Brinell Value	3, 7
Joint	Woodloc® 5S
Floor heating	Yes
Warranty	30 years
Wear-layer material	Hardwood
Wear-layer thickness	3, 5 mm
Core material	Pine/Spruce/Alder
Backside material	Spruce
Thickness	15 mm
Installation method	Floating, glue-down
EAN Code	7393969044240

### TECHNICAL PROPERTIES

Moisture content	EN13183	7%±2%
Minimum Mean Density kg/m <sup>3</sup>		>500 kg/m <sup>3</sup>
Reaction To Fire	EN13501-1	Dfl-s1
Formaldehyde Emission	EN717-1	E1
Content PCP	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
Breaking Strength N/mm <sup>2</sup>	EN1533	NPD
Thermal Conductivity	EN12664	0,14 W/mK
Thermal Resistance R-Value		.11 (m <sup>2</sup> K/W)
Biological Durability	EN350-2	Class 1
CARB2		Compliant

### CERTIFICATES

