



## OAK ESTORIL

This classic, 2-strip oak floor from the Sand Collection has a soft white stain, which enhances the organic design and darker knots featured in the timber. Four-sided micro-bevelling at the edges ensures a classic, full plank look and feel. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

| PRODUCT DESCRIPTION  |                                | FACTS                |                     | TECHNICAL PROPERTIES                   |             |                          |  |
|--|--------------------------------|----------------------|---------------------|--|-------------|--------------------------|--|
| Article Number   | 151N8AEKFKW220                 | Wood Species         | Oak                 | Moisture content                       | EN13183     | 7%±2%                    |  |
| Surface treatment  | Oil                            | Board                | 1-strip             | Minimum Mean Density kg/m <sup>3</sup> |             | >500 kg/m <sup>3</sup>   |  |
| Design features  | Microbevelled 4-sided, brushed | Grading              | Lively (Country)    | Reaction To Fire                       | EN13501-1   | Dfl-s1                   |  |
| Dimensions   | 2266 x 187 x 15 mm             | Range                | Kährs Original      | Formaldehyde Emission                  | EN717-1     | E1                       |  |
| Weight per Package   | 21 kg                          | Collection           | Sand Collection     | Content PCP                            | CEN/TR14823 | ≤ 5 x 10-6n              |  |
| Status in Movex  | 20                             | Resandable           | 2-3 times           | Breaking Strength N/mm <sup>2</sup>    | EN1533      | NPD                      |  |
| Area per Package   | 2.54 m <sup>2</sup>            | Natural/Stained      | Stained             | Thermal Conductivity                   | EN12664     | 0,14 W/mK                |  |
| Area Per Board   | 0.423 m <sup>2</sup>           | Brinell Value        | 3, 7                | Thermal Resistance R-Value             |             | .11 (m <sup>2</sup> K/W) |  |
| <b>DETAIL DESCRIPTION</b><br>Naturally occurring wood colour variations allowed, from light to dark brown. The product includes large sound and black knots. Knots may vary in size and numbers. |                                | Joint                | Woodloc® 5S         | Biological Durability                  | EN350-2     | Class 1                  |  |
|  |                                | Floor heating        | Yes                 | <b>CARB2</b>                           |             | Compliant                |  |
|  |                                | Warranty             | 30 years            |  |             |                          |  |
|  |                                | Wear-layer material  | Hardwood            |  |             |                          |  |
|  |                                | Wear-layer thickness | 3, 5 mm             |  |             |                          |  |
|  |                                | Core material        | Pine/Spruce lamella |  |             |                          |  |
| <b>COLOUR CHANGE</b><br>Stained product - noticeable color change over time.   |                                | Thickness            | 15 mm               |  |             |                          |  |
|  |                                | Installation method  | Floating, glue-down |  |             |                          |  |
|  |                                | EAN Code             | 7393969041249       |  |             |                          |  |
|  |                                | Surface Colour       | White E0V           |  |             |                          |  |

### CERTIFICATES

