



OAK FAWN

This plank oak floor from the Canvas Collection features a warm, white-pigmented matt lacquer. The result is a beautifully neutral floor with the appearance of freshly cut wood. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. The matt lacquer eliminates glare while protecting the wood from daily wear. Four-sided micro-bevelling at the edges ensures a classic full plank look and feel.

PRODUCT DETAILS

| | |
|---|---|
| Article Number | 13103AEK1KKW185 |
| EAN Code | 7393969048040 |
| Surface treatment | Matt lacquer |
| Design features | Microbevelled 4-sided, Brushed |
| Dimensions | 1860 x 127 x 13 mm |
| Weight per Package (kg) | 12.687 kg |
| Area per Package (m²) | 1.652 m ² |
| Area per pallet (m²) | 104.076 m ² |
| Package info | Packages may contain start and stop boards. |

DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark. Small sized knots in limited numbers allowed.

COLOUR CHANGE

Stained product - noticeable color change over time.

FACTS

| | |
|-----------------------------|---------------------|
| Wood Species | Oak |
| Board | 1-strip |
| Grading | Variation |
| Range | Kährs Avanti |
| Collection | Canvas Collection |
| Resandable | 2-3 times |
| Natural/Stained | Stained |
| Brinell Value | 3,7 |
| Joint | Woodloc® 5G |
| Floor heating | Yes |
| Warranty | 25 years |
| Wear-layer material | Hardwood |
| Wear-layer thickness | 3 mm |
| Core material | Pine/Spruce lamella |
| Thickness | 13 mm |
| Surface Colour | White |
| Installation method | Floating, Glue-down |

TECHNICAL PROPERTIES

| | | |
|--|--------------------------|--------------------------|
| Moisture content | EN13183 | 7%±2% |
| Minimum Mean Density kg/m³ | >500 kg/m ³ | |
| Reaction To Fire | EN13501-1 | Dfl-s1 |
| Formaldehyde Emission | EN717-1 | E1 |
| Content PCP | CEN/TR14823 | ≤ 5 x 10 ⁻⁶ n |
| Breaking Strength N/mm² | EN1533 | NPD |
| Thermal Conductivity | EN12664 | 0,08 W/mK |
| Thermal Resistance R-Value | .15 (m ² K/W) | |
| Biological Durability | EN350-2 | Class 1 |
| CARB2 | Compliant | |



Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.