



OAK FREDRIK

The beige-brown hues in this single-strip floor from the Founders Collection are accentuated by its rich smoked finish, resulting in a warm, rustic expression. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES	
Article Number	151N7BEKFKW240	Wood Species	Oak	Moisture content	EN13183 7%±2%
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m³	>500 kg/m³
Design features	Bevelled 4-sided, handscraped, brushed, smoked	Grading	Dynamic	Reaction To Fire	EN13501-1 Dfl-s1
Dimensions	2420 x 187 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1 E1
Weight per Package	22 kg	Collection	Founders Collection	Content PCP	CEN/TR14823 ≤ 5 x 10-6n
Area per Package	2.72 m²	Resandable	2-3 times	Breaking Strength N/mm²	EN1533 NPD
Area Per Board	0.453 m²	Natural/Stained	Natural	Thermal Conductivity	EN12664 0,14 W/mK
		Brinell Value	3, 7	Thermal Resistance R-Value	.11 (m2K/W)
		Joint	Woodloc® 5S	Biological Durability	EN350-2 Class 1
		Floor heating	Yes	CARB2	Compliant
		Warranty	30 years		
		Wear-layer material	Hardwood		
		Wear-layer thickness	3, 5 mm		
		Core material	Pine/Spruce lamella		
		Backside material	HardwoodHardwood		
		Thickness	15 mm		
		Installation method	Floating, glue-down		
		EAN Code	7393969036047		
		Surface Colour	Dark Brown FC		
DETAIL DESCRIPTION		CERTIFICATES			
<p>All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The smoked design is likely to enhance the naturally occurring wood color variations and create further contrast between light and dark. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.</p>					
COLOUR CHANGE					
Smoked product - noticable color change over time.					

