



OAK INDIETRO

This smoked, 3-strip floor from the Da Capo collection features an intentional colour variation in the boards, ranging from bleached blonde to rich carob hues to create a dramatic and weathered look. The knots, cracks and discolourations in the boards result in a beautifully aged expression. Each plank is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	153XCDEKRNKW190	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Oil	Board	3-strip	Minimum Mean Density kg/m ³		>500 kg/m ³
Design features	Brushed, saw marks, smoked	Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1900 x 190 x 15 mm	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1
Weight per Package	19 kg	Collection	Da Capo Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	2.17 m ²	Resandable	2-4 times	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.361 m ²	Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m ² K/W)
		Joint	Woodloc®	Biological Durability	EN350-2	Class 1
COLOUR CHANGE		Floor heating	Yes	CARB2		Compliant
		Warranty	30 years			
		Wear-layer material	Hardwood			
		Wear-layer thickness	3, 5 mm			
		Core material	Pine/Spruce lamella			
Backside material	Veneer					
CERTIFICATES		Thickness	15 mm			
		Installation method	Glue-down, floating			

Some muting of colour variation to medium, straw brown.

CERTIFICATES

