



## OAK KLINTA

The transparent white stain on this single-strip oak floor from the Småland Collection creates a natural pale impression. Each board is meticulously hand-scraped which highlights the knots and the balanced rustic appearance of the floor. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Every board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

### PRODUCT DESCRIPTION

<b>Article Number</b>	151NCSEK07KW240
<b>Surface treatment</b>	Oil
<b>Design features</b>	Bevelled 4-sided, brushed, handscraped
<b>Dimensions</b>	2420 x 187 x 15 mm
<b>Weight per Package</b>	22 kg
<b>Area per Package</b>	2.72 m <sup>2</sup>
<b>Area Per Board</b>	0.453 m <sup>2</sup>

### DETAIL DESCRIPTION

All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.

### COLOUR CHANGE

Stained product - noticeable color change over time.

### FACTS

<b>Wood Species</b>	Oak
<b>Board</b>	1-strip
<b>Grading</b>	Dynamic
<b>Range</b>	Kährs Supreme
<b>Collection</b>	Småland Collection
<b>Resandable</b>	2-4 times
<b>Natural/Stained</b>	Stained
<b>Brinell Value</b>	3, 7
<b>Joint</b>	Woodloc® 5S
<b>Floor heating</b>	Yes
<b>Warranty</b>	30 years
<b>Wear-layer material</b>	Hardwood
<b>Wear-layer thickness</b>	3, 5 mm
<b>Core material</b>	Pine/Spruce lamella
<b>Backside material</b>	Veneer
<b>Thickness</b>	15 mm
<b>Installation method</b>	Floating, glue-down
<b>EAN Code</b>	7393969044820
<b>Surface Colour</b>	White

### TECHNICAL PROPERTIES

<b>Moisture content</b>	EN13183	7%±2%
<b>Minimum Mean Density kg/m<sup>3</sup></b>		>500 kg/m <sup>3</sup>
<b>Reaction To Fire</b>	EN13501-1	Dfl-s1
<b>Formaldehyde Emission</b>	EN717-1	E1
<b>Content PCP</b>	CEN/TR14823	≤ 5 x 10 <sup>-6</sup> n
<b>Breaking Strength N/mm<sup>2</sup></b>	EN1533	NPD
<b>Thermal Conductivity</b>	EN12664	0,14 W/mK
<b>Thermal Resistance R-Value</b>		.11 (m <sup>2</sup> K/W)
<b>Biological Durability</b>	EN350-2	Class 1
<b>CARB2</b>		Compliant

### CERTIFICATES

