



OAK RITORNO

This oiled, 3-strip floor from the Da Capo collection features an intentional colour variation in the boards, ranging from foggy grey to wet sand hues to create a dramatic and weathered look. The knots, cracks and discolourations in the boards result in a beautifully aged expression. Each plank is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES			
Article Number	153XCDEKGGKW190	Wood Species	Oak	Moisture content	EN13183	7%±2%	
Surface treatment	Oil	Board	3-strip	Minimum Mean Density kg/m ³		>500 kg/m ³	
Design features	Brushed, saw marks	Grading	Expressive	Reaction To Fire	EN13501-1	Dfl-s1	
Dimensions	1900 x 190 x 15 mm	Range	Kährs Supreme	Formaldehyde Emission	EN717-1	E1	
Weight per Package	19 kg	Collection	Da Capo Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n	
Area per Package	2.17 m ²	Resandable	2-4 times	Breaking Strength N/mm ²	EN1533	NPD	
Area Per Board	0.361 m ²	Natural/Stained	Stained	Thermal Conductivity	EN12664	0,14 W/mK	
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Resistance R-Value		.11 (m ² K/W)	
		Joint	Woodloc®	Biological Durability	EN350-2	Class 1	
COLOUR CHANGE		Floor heating	Yes	CARB2			
		Warranty	30 years	Compliant			
		Wear-layer material	Hardwood				
		Wear-layer thickness	3, 5 mm				
		Core material	Pine/Spruce lamella				
		Backside material	Veneer				
		Thickness	15 mm				
Installation method	Glue-down, floating						
		Surface Colour	Grey				

CERTIFICATES

