



OAK STRAW

The naturally oiled finish on this rustic, single-strip oak floor from the Artisan Collection brings out the colour variations in the timber, which range from toasted cinnamon to burnt toffee hues. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel. Hand-scraping enhances the worn appearance of the floor.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES			
Article Number	151XCDEKFZKW190	Wood Species	Oak	Moisture content	EN13183	7%±2%	
Surface treatment	Oil	Board	1-strip	Minimum Mean Density kg/m ³		>500 kg/m ³	
Design features	Bevelled 4-sided, brushed, handscraped	Grading	Dynamic	Reaction To Fire	EN13501-1	Dfl-s1	
Dimensions	1900 x 190 x 15 mm	Range	Kährs Original	Formaldehyde Emission	EN717-1	E1	
Weight per Package	17 kg	Collection	Artisan Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n	
Area per Package	2.17 m ²	Resandable	2-3 times	Breaking Strength N/mm ²	EN1533	NPD	
Area Per Board	0.361 m ²	Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK	
DETAIL DESCRIPTION All naturally occurring wood colour variations allowed, from light to dark brown. Sapwood may occur. The product includes very large sound and black knots and cracks. Knots and cracks will be present in all sizes and numbers.		Joint	Woodloc®	Thermal Resistance R-Value		.11 (m ² K/W)	
		Floor heating	Yes	Biological Durability	EN350-2	Class 1	
		Warranty	30 years	CARB2		Compliant	
		Wear-layer material	Hardwood				
		Wear-layer thickness	3,5 mm				
		Core material	Pine/Spruce lamella				
		Thickness	15 mm				
		Installation method	Glue-down, floating				
		EAN Code	7393969031349				
		Surface Colour	Rustic natur				

COLOUR CHANGE

Some muting of colour variation to medium, straw brown.

CERTIFICATES

