



REEF OAK

The natural shades of this oak single-strip floor in the Unity Collection, range from subtle tawny to sunset umbers and chocolate browns with just a few scattered knots. The matt lacquer finish eliminates glare while protecting the wood from daily wear. Each board is carefully brushed to bring out the character of the grain and highlight the natural texture of the wood. Four-sided bevelling at the edges ensures a classic, full plank look and feel.

PRODUCT DESCRIPTION		FACTS		TECHNICAL PROPERTIES		
Article Number	101P3AEK09KW120	Wood Species	Oak	Moisture content	EN13183	7%±2%
Surface treatment	Matt lacquer	Board	1-strip	Minimum Mean Density kg/m ³		>800 kg/m ³
Design features	Bevelled 4-sided, brushed	Grading	Variation (Town)	Reaction To Fire	EN13501-1	Dfl-s1
Dimensions	1200 x 125 x 10 mm	Range	Kährs Spirit	Formaldehyde Emission	EN717-1	E1
Weight per Package	14 kg	Collection	Unity Collection	Content PCP	CEN/TR14823	≤ 5 x 10-6n
Area per Package	1.50 m ²	Resandable	1 time	Breaking Strength N/mm ²	EN1533	NPD
Area Per Board	0.150 m ²	Natural/Stained	Natural	Thermal Conductivity	EN12664	0,14 W/mK
DETAIL DESCRIPTION		Brinell Value	3, 7	Thermal Resistance R-Value		.07 (m ² K/W)
		Joint	Woodloc®	Biological Durability	EN350-2	Class 1
Even colour with minor variations. Small sized knots in limited numbers allowed.		Floor heating	Yes	CARB2		Compliant
		Warranty	20 years			
COLOUR CHANGE		Wear-layer material	Hardwood			
		Wear-layer thickness	1, 9 mm			
Some muting of colour variation to medium, straw brown.		Core material	HDF			
		Backside material	Veneer			
		Thickness	10 mm			
		Installation method	Floating, glue-down			
		EAN Code	7393969030601			

CERTIFICATES

